

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65D 43/16, 33/25, 1/22	A1	(11) International Publication Number: WO 00/64772 (43) International Publication Date: 2 November 2000 (02.11.00)
--	----	---

(21) International Application Number: PCT/US00/09639

(22) International Filing Date: 11 April 2000 (11.04.00)

(30) Priority Data:
09/296,815 22 April 1999 (22.04.99) US

(71) Applicant: THE PROCTER & GAMBLE COMPANY
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH
45202 (US).


(72) Inventors: RANDALL, Catherine, Jean; 3202 Ashwood Drive,
Cincinnati, OH 45213 (US). HUPP, Matthew, Todd; 11624
Timber Ridge Lane, Apt. #3, Sharonville, OH 45241 (US).
KERFOOT, Jennifer, Kay; 517 S. Cuyler Avenue, Apt.
#1N, Oak Park, IL 60304 (US).

(74) Agents: REED, T., David et al.; The Procter & Gamble
Company, 5299 Spring Grove Avenue, Cincinnati, OH
45217-1087 (US).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU,
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ
(Utility model), DE, DE (Utility model), DK, DK (Utility
model), DM, EE, EE (Utility model), ES, FI, FI (Utility
model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS,
JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ,
TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO
patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF,
BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN,
TD, TG).

Published
With international search report.

(54) Title: STACKABLE, SELF-SUPPORTING CONTAINER WITH SLIDING MECHANICAL CLOSURE



(57) Abstract

The present invention provides a container (10) comprising: (a) a semi-enclosed container body including a tubular structure having two open ends and a bottom panel enclosing one end of the container body, the other end of the tubular structure opposite from the bottom panel forming a substantially continuous outwardly-extending peripheral flange (25); (b) a lid (40) for selectively converting the semi-enclosed container to a closed container; and (c) a closure means (30) for sealing the lid to the container body, the closure means comprising a mechanical interlocking seal and a slideable mechanical closure (36) for sealing the mechanical interlocking seal. The container is preferably stackable and self-supporting, and the mechanical interlocking seal includes at least one interlocking bead and groove pair located on the lid and flange. The container may also be collapsible via folding of the tubular structure.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

STACKABLE, SELF-SUPPORTING CONTAINER
WITH SLIDING MECHANICAL CLOSURE

FIELD OF THE INVENTION

The present invention relates to storage containers, particularly those suitable for use in the containment and protection of various items including perishable materials. The present invention further relates to such storage containers having improved sealability for containment and protection of items contained within under a wide range of in-use conditions.

BACKGROUND OF THE INVENTION

Flexible storage bags for use in the containment and protection of various items, as well as the preservation of perishable materials such as food items, are well known in the art. Such bags typically comprise a rectangular sheet of polymeric film folded upon itself and sealed along two edges to form a semi-enclosed container having two flexible opposed sidewalls, three sealed or folded edges, and one open edge. A closure integrally formed with the bag such as an interlocking rib-type seal or separately provided such as a plastic or paper-clad-wire tie completes the containment assembly. Sliding closure mechanisms, which utilize a sliding plastic sleeve to force interlocking ribs into and out of engagement, have become popular due to their comparative ease of operation and visual and tactile confirmation that opening and closing operations have been successfully completed.

As utilized herein, the term "flexible" is utilized to refer to materials which are capable of being flexed or bent, especially repeatedly, such that they are pliant and yieldable in response to externally applied forces. Accordingly, "flexible" is substantially opposite in meaning to the terms inflexible, rigid, or unyielding. Materials and structures which are flexible, therefore, may be altered in shape and structure to accommodate external forces and to conform to the shape of objects brought into contact with them without losing their integrity. Flexible storage bags of the foregoing variety are typically formed from polymeric film, such as polyethylene or other members of the polyolefin family, in thicknesses of between about 0.0002 inches to about 0.002 inches. Such films are frequently transparent but sometimes are opaque and/or colored.

Flexible storage bags of the currently commercially available variety provide a means of conveniently storing a wide range of objects and materials in a generally

Flexible storage bags of the currently commercially available variety provide a means of conveniently storing a wide range of objects and materials in a generally disposable containment device. While flexible storage bags of the foregoing variety have enjoyed a fair degree of commercial success, it is often difficult to utilize them in situations where items or materials, especially liquids, must be poured into them while holding the mouth of the bag in a sufficiently open condition. The flexible nature of the bags, while in some regards highly advantageous, tends to require human or mechanical intervention to hold them open for filling.

With regard to rigid or semi-rigid containers, it is well recognized that such containers have also realized a fair degree of commercial success in providing a means for storing a wide variety of contents. Such containers typically have an opening which maintains an open condition for filling and are typically self-supporting with the opening in the proper orientation for filling. Such containers also are frequently provided with flat bottoms and tops to provide stackability. However, such containers are typically constructed of more expensive materials such that disposability is limited. Further, such containers and lids are usually sealed by an interlocking mechanical closure involving interlocking beads and grooves. While such mechanical closures can be effective in preserving container contents, some consumers experience difficulty in fully completing the closure operation and confirming for themselves that a satisfactory closure has been achieved. This is particularly so when the physical change in position of the lid between interlocked and non-interlocked positions is comparatively small.

Accordingly, it would be desirable to provide a storage container combining the desirable qualities of both flexible bags and storage containers and minimizing the less desirable qualities of both approaches.

More particularly, it would be desirable to provide a storage container having improved sealability in use.

It would be yet further desirable to provide such a container which provides visual and/or tactile confirmation to the consumer that a satisfactory closure has been achieved.

SUMMARY OF THE INVENTION

The present invention provides a container comprising: (a) a semi-enclosed container body including a tubular structure having two open ends and a bottom panel enclosing one end of the container body, the other end of the tubular structure opposite from the bottom panel forming a substantially continuous outwardly-extending peripheral flange; (b) a lid for selectively converting the semi-enclosed container to a closed

container; and (c) a closure means for sealing the lid to the container body, the closure means comprising a mechanical interlocking seal and a slideable mechanical closure for sealing the mechanical interlocking seal.

The container is preferably stackable and self-supporting, and the mechanical interlocking seal includes at least one interlocking bead and groove pair located on the lid and flange. The container may also be collapsible via folding of the tubular structure.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming the present invention, it is believed that the present invention will be better understood from the following description in conjunction with the accompanying Drawing Figures, in which like reference numerals identify like elements, and wherein:

Figure 1 is a perspective view of a storage container in accordance with the present invention in a closed condition;

Figure 2 is a perspective view of the storage container of Figure 1 in an open condition and partially filled with solid objects;

Figure 3 is a plan view of a storage container similar to that of Figure 1;

Figure 4 is a perspective view of a representative slider element in accordance with the present invention;

Figure 5 is an elevational view of the slider of Figure 4;

Figure 6 is an elevational sectional view taken along line 6-6 of Figure 5;

Figure 7 is a perspective view of the storage container of Figure 1 in a horizontal position in preparation for folding;

Figure 8 is a perspective view of the storage container of Figure 1 in a partially folded and collapsed condition; and

Figure 9 is a perspective view of the storage container of Figure 1 in a fully folded and collapsed condition.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 depicts a presently preferred embodiment of a storage container 10 according to the present invention. In the embodiment depicted in Figure 1, the storage container 10 includes a container body 20 preferably unitarily formed from a piece of sheet material and a lid 40 preferably unitarily formed with the container body 20 or at least hingedly attached to the container body at hinge line 45. Storage container 10 also includes closure means 30 located adjacent to edge 28 for sealing the peripheral portions of the lid 40 and container body 20 to form a fully-enclosed container or vessel as shown

in Figure 1. Closure means 30 comprises the marginal portion of the lid 40 and the marginal flange portion 25 of the container body 20. Closure means 30 is selectively openable, sealable, and resealable, as will be described hereinafter. Hinge line 45 shown in Figure 2 preferably comprises a unitary living hinge, and may optionally be provided as a line of weakness by scoring, perforations, or the like which may optionally permit the lid to be separated from the container body.

In the preferred configuration depicted in Figure 1, the closure means 30 closure means is disposed along all portions of edge 28 except the hinged portion at hinge line 45. However, under some circumstances a closure means formed by a greater degree of encirclement (such as, for example, a closure means which completely encircles the opening in the absence of a hinge line) may provide adequate closure integrity. The flange 25 may be either unitarily formed with the container body 20 or provided as a separate material element joined to the container body. When provided as a separate, preferably more rigid material element, it is presently preferred that the container body material be formed into at least a small peripheral flange at its upper edge (defining the opening) with pleated corners so as to form a suitable junction point for joining the container body to the flange.

As shown in Figure 1, the closure means 30 comprises a mechanical interlocking seal which includes at least one mating or interlocking bead 32 and groove 34 pair of elements on mating portions of the flange 25 and lid 40. In a presently preferred embodiment, the bead 32 is unitarily formed with and projects upwardly from the flange 25 around the three free sides of the flange (i.e., not necessarily around the rear portion of the container behind the hinge) while the groove 34 has a complementary shape which is open on the bottom so as to receive the bead 32 therein. The closure means 30 also includes a sliding mechanical element or slider 36 which is captively engaged with the bead and groove so as to remain attached to the container unless one or more elements is deformed to permit its removal. Slider 36 is sized and shaped so as to be freely slideable over the bead and groove when they are fully engaged with one another to effect a sufficient closure seal. Slider 36 therefore functions to seal the bead and groove into one another when it is drawn around the periphery of the container from one side to another after the container has been opened.

Figure 4 is an elevational perspective view of a preferred embodiment of a sliding mechanical element, or slider, 36 in accordance with the present invention. As shown in Figure 4, and more prominently in Figure 5, the slider 36 has a generally C-shaped configuration such that the ends of the slider can extend inwardly over the peripheral edges of the flange 25 and lid 40 in overlying relation to the bead 32 and groove 34. The

portions of the slider 36 which overlie the bead and groove have a spacing therebetween which is sufficiently small as to force the bead and groove into interlocking engagement when the slider is translationally drawn over a region of the periphery where the bead and groove are separated.

The bead and groove are preferably spaced a substantially constant distance inwardly from the peripheral edge of the lid and flange such that a slider having an adequate inward extent can be drawn around the peripheral edge of the container without leaving gaps or unsealed portions of the bead and groove pair. In addition, while the closure mechanism of the present invention may be employed on containers having a circular, oval, elliptical, or other curvilinear cross-section, the closure mechanism of the present invention may be employed as shown in Figures 1-3 on containers of polygonal cross-section, such as rectangular and square containers, so long as the corners of the flange and lid, as well as the bead and groove pair, are suitably radiused at the corners so that their radius exceeds the minimum necessary for the slider to change direction.

In addition, while the present invention has been illustrated and described in the context of a container having a single bead and groove pair, other arrangements may be employed wherein one or more sliders may engage one or more mating pairs of beads and grooves where the beads and grooves are side by side to form consecutive seals, where they are end to end, or where they occupy separate unconnected regions of the container.

Storage container 10 is suitable for containing and protecting a wide variety of materials and/or objects contained within the container body. Figure 2 depicts the storage container 10 in an open condition wherein the closure means 30 has been released such that edge 28 may be opened to admit materials and/or objects into the interior of the body portion of the storage container 10. In Figure 2 a plurality of generic solid objects 99 are shown within the storage container 10.

Lid 40 is preferably of unitary construction and comprises a central lid panel 42 and a lid frame 44, either of which may be formed of various elements if desired. The ability to construct the container of multiple composite elements permits the use of diverse materials such as transparent polymeric panels for lid panels or more rigid, resilient materials for flanges and lid frames independently of the tailoring of materials for the container body 20. As best shown in Figures 1 and 2, the central lid panel 42 preferably extends downwardly to form a pan-shaped lid which forms a plug seal by fitting into a complementary recess or shelf in the upper portion of the container body for enhanced sealing capability.

In the embodiment of Figure 1, the storage container 10 comprises two generally planar end panels 50, two generally planar, gusseted side panels 60, and a generally planar bottom panel 70, which panels form a semi-enclosed container having an opening defined by upper flange 25. End panels 50 include side edges 55 and bottom edges 54, while side panels 60 include bottom edges 64 and gussets having converging base creases 62 and medial creases 61, with lateral creases 63. The creases are preferably formed into the material as lines of weakness via molding thinned areas into the material, scoring, or other suitable methods. In the configuration depicted in Figure 1, the storage container is in its self-supporting, open condition. Flange 25 is preferably sufficiently resilient and rigid to aid in holding the open end of the container in an open condition as shown in Figure 1.

While the storage container described above with regard to Figure 1 provides many advantages compared with flexible storage bags and storage containers commonly available, it also includes additional features to enable the container to assume a self-supporting configuration to facilitate product access and product filling without manual support for greater ease of use.

As utilized herein, the term "self-supporting" is utilized to refer to materials, structures, or containers which are capable of maintaining their orientation in a plane parallel to the direction of the force of gravity. For example, a self-supporting material, particularly a sheet material, may be held so that it extends upwardly parallel to the direction of the force of gravity and maintain its orientation without folding over or collapsing. Non-self-supporting materials typically will fold over or collapse and not be capable of being held parallel to the force of gravity (i.e., "vertically") unless they are held so that they extend downwardly from their point of support. Correspondingly, a self-supporting bag or container is capable of maintaining its orientation with surfaces extending upwardly from their base of support in opposition to the force of gravity without folding over upon itself or collapsing.

In addition to being self-supporting, gusseted storage container 10 is also preferably readily foldable or collapsible to provide easy storage occupying minimal space. Figure 7 depicts a gusseted storage container 10 as shown in Figure 1 positioned laterally on its side in preparation for folding. Figure 8 depicts a gusseted storage container 10 as shown in Figure 1 but in a partially folded or collapsed condition. Accordingly, medial creases 61 have been pushed inwardly toward one another, bringing bottom edges 64 toward and generally parallel to the flange 25. Figure 9 shows a gusseted storage container 10 in a more fully folded condition wherein folding continues until the bottom 70 is substantially parallel to and in close proximity to the flange 25 and

the end panels are fully folded inwardly toward one another. Medial creases 61 could also be folded outwardly, if desired, which provides the additional feature of helping to erect the container when they are pushed inwardly. Also depicted in Figure 7 is the optional reinforcing panel 72 which adds additional integrity and stability to the generally rectangular, planar bottom panel 70. To avoid negatively impacting upon the foldability of the container body, the reinforcing bottom panel 72 preferably includes creases which substantially align with lateral creases 63 for folding as depicted in Figures 7-9 or preferably is located between the creases 63, as shown.

The addition of additional reinforcement to the bottom panel lowers the center of gravity of the empty container for greater stability prior to and during filling, increases the stiffness of the bottom of the container for added stability in most circumstances filled or empty, and reduces the likelihood of the bottom of the container bowing when filled with heavier contents. The reinforcing panel may be of a similar material to the container body material or may be of a different more or less durable material, and is secured to the bottom panel by adhesive application or other suitable means. It is presently preferred that when a reinforcing panel is employed that it be placed on the exterior surface of the bottom panel rather than on the interior surface in order to provide support and reinforcement without adding additional surfaces, joints, and crevices on the interior of the container where they may provide sites for trapping portions of the contents and creating cleaning difficulties.

The flexible sheet material utilized to form the body of the container is sufficiently flexible and yieldable to accommodate the folding or collapsing of the container body between the open configuration of Figure 1 and the closed configuration of Figure 9. More particularly, the side panels 60 are sufficiently flexible to fold or pleat upon themselves as the end panels 50 pivot inwardly toward one another as the bottom panel 70 moves toward the lid 40.

Various compositions suitable for constructing the storage containers of the present invention include substantially impermeable materials such as polyvinyl chloride (PVC), polyvinylidene chloride (PVDC), polyethylene (PE), polypropylene (PP), aluminum foil, coated (waxed, etc.) and uncoated paper, coated nonwovens etc., and substantially permeable materials such as scrims, meshes, wovens, nonwovens, or perforated or porous films, whether predominantly two-dimensional in nature or formed into three-dimensional structures. Such materials may comprise a single composition or layer or may be a composite structure of multiple materials, including a substrate material utilized as a carrier for a substance. Materials found suitable for use in accordance with

the present invention include a low density polyethylene film, 10 mil thickness, commercially available from Chevron under the manufacturer's designation PE1122.

Materials utilized as a closure means in accordance with the present invention may be unitarily formed and constructed as part of the body of the storage container either before, during, or after assemblage of the container from its material components. Alternatively, such closure means may also be separately formed and joined to the body of the storage container either before, during or after assemblage of the container. The material utilized for the closure means may be the same as or different from the material utilized to form the container body either in dimensions or in composition. The closure means may also incorporate additional features such as texture for providing an audible or tactile signal when the slider is utilized or different colors on the bead and groove which yield a different color appearance when engaged (similar to commercially available closures on flexible bags).

In accordance with the present invention, the closure means 30 provides the user with an easy-to-operate closure means for closing and sealing an opening in a storage container. The closure means 30 is easy to manipulate, as the only dexterity required is to grasp or pinch the slider with a pair of opposed digits and move the slider across the extent of the opened portion of the lid to provide secure engagement of the bead and groove, thereby converting the storage container from a semi-enclosed container to a fully closed container. To open the storage container of Figure 1, a user may grasp a pair of opposing tabs 35 and pull them in opposite directions to initiate and propagate separation of the opposed halves of flange 31, and hence closure means 30. In order to avoid conflicts between the tabs and the operation of the slider, the tabs are preferably formed from the flange and lid material by removing portions thereof to leave isolated projections which project no further than the outer edge of the flange. As shown in the Figures, a sinusoidal edge for the flange and a phase-shifted sinusoidal edge for the lid have proven satisfactory.

In addition to such use of sheet material folded and sealed to form the container body, the container body may be constructed in any known and suitable fashion such as those known in the art for making such containers in commercially available form. Heat or adhesive sealing technologies may be utilized to join various components or elements of the container to themselves or to each other. In addition, the container bodies may be thermoformed, blown, or otherwise molded from a starting blank or sheet of material rather than reliance upon folding and bonding techniques to construct the container bodies from a web or sheet of material.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

WHAT IS CLAIMED IS:

1. A container comprising:
 - (a) a semi-enclosed container body including a tubular structure having two open ends and a bottom panel enclosing one end of said container body, the other end of said tubular structure opposite from said bottom panel forming a substantially continuous outwardly-extending peripheral flange;
 - (b) a lid for selectively converting said semi-enclosed container to a closed container; and
 - (c) a closure means for sealing said lid to said container body, said closure means comprising a mechanical interlocking seal and a slideable mechanical closure for sealing said mechanical interlocking seal.
2. The container of Claim 1 wherein said closure means includes at least one interlocking bead and groove pair located on said lid and said flange and a slideable mechanical closure for engaging said interlocking bead and groove pair.
3. The container of Claim 1, wherein said interlocking bead and groove pair define at least two orthogonal linear segments in a plane defined by said flange.
4. The container of Claim 1, wherein at least one of said lid and said flange include tabs, said tabs projecting no farther outwardly than an outer edge of said flange.
5. The container of Claim 1, wherein said tubular structure includes two opposed side walls, two opposed end walls between said side walls, said side walls and said end walls together forming said tubular structure.
6. The container of Claim 5, wherein said side walls, said end walls, and said bottom panel are unitarily formed from a continuous sheet of material.
7. The container of Claim 5, wherein each of said side walls includes a gusset extending in a direction substantially parallel to said bottom panel, and wherein said side walls are inwardly or outwardly foldable and said end walls are inwardly foldable toward one another, such that said container is collapsible in a direction normal to said lid and said bottom panel while being substantially self-supporting while said side walls and said end walls are in their unfolded orientation.

8. The container of Claim 1, wherein said lid is joined to said container via a hinge, and said interlocking bead and groove pair extend outwardly beyond said hinge.
9. The container of Claim 1, wherein said tubular structure has a substantially rectangular cross-sectional shape.
10. The container of Claim 1, wherein said container is stackable and self-supporting.

Fig. 1





Fig. 2



2/3




Fig. 3




Fig. 4




Fig. 5

Fig. 6

3/3




Fig. 7




Fig. 8




Fig. 9

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/09639

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B65D43/16 B65D33/25 B65D1/22		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 B65D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EP0-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 246 288 A (SANBORN) 20 January 1981 (1981-01-20)	1,2,5,6, 9,10
Y	column 5, line 9 -column 6, line 52; figures 5,7-10	4,7,8
A	US 5 788 378 A (THOMAS) 4 August 1998 (1998-08-04) claim 1; figures	1
A	WO 97 42090 A (RUBEN) 13 November 1997 (1997-11-13) abstract; claim A	1,3
Y	FR 2 116 203 A (PLASTICFORMING) 13 July 1972 (1972-07-13)	4
A	figures	10
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "g" document member of the same patent family		
Date of the actual completion of the international search 19 July 2000		Date of mailing of the international search report 28/07/2000
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Newell, P

INTERNATIONAL SEARCH REPORT

Intern 1al Application No

PCT/US 00/09639

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 735 423 A (BLACK) 7 April 1998 (1998-04-07) claim 1; figures 3,6-9 -----	7,8

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern 1st Application No

PCT/US 00/09639

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4246288 A	20-01-1981	AU 530798 B AU 6109280 A CA 1224756 A DE 3029596 A FR 2463072 A GB 2057388 A, B IT 1132385 B JP 56041167 A	28-07-1983 12-02-1981 28-07-1987 26-02-1981 20-02-1981 01-04-1981 02-07-1986 17-04-1981
US 5788378 A	04-08-1998	AU 4501497 A EP 0934209 A WO 9813271 A	17-04-1998 11-08-1999 02-04-1998
WO 9742090 A	13-11-1997	AU 2999697 A US 5964399 A	26-11-1997 12-10-1999
FR 2116203 A	13-07-1972	NONE	
US 5735423 A	07-04-1998	NONE	